



Altair® IGLU® Louvre Single Bay Component Form

Email: sales@breezway.com.au

QUOTE

ORDER



Version: April 2025

Date:	Customer Name:	Contact Name:
Required Despatch Date:	Despatch to:	Contact Number:
Customer Order Number:		Transport Method:
Job Reference:		Email/fax:

Please Note:

Special Instructions:

Colour	Handle Colour	Fixing Method	Keylock (Manual Only)	ULS (Pa)	Water (Pa)
		Screw Holes	No		

Operation	Daylight Height (mm)	Daylight Width (mm)	Handle Side	Restricted Opening	Security Bars	Quantity	Markings
Standard Handle			Left				

IGLU Quote and Order Instructions & Notes

- Selected 'Operation' (Column A) will determine what selections can be made for following cells.
- IGLU Double Glazed Louvre Blade standard spans are:
 - 300mm (not compatible with Powerlouvre)
 - 500mm
 - 800mm
 - 1,127mm
- All IGLU assemblies utilise high profile sills
- All IGLU Clips and weatherstrip inserts are Black
- Always compare intended window sizes to Breezway Product Performance Warranty to ensure site suitability.
- 72mm restricted opening required for Fall Prevention compliance.
- Variable Handle Positions are available. Due to blade weight the following maximum handle to blade ratios apply depending on blade span.
 - 300mm & 500mm blades: Up to 9 Blades per handle
 - 800mm blades: Up to 6 blades per handle
 - 1,127mm blades: Up to 5 blades per handle

Accessories	Length (mm)	Quantity	Accessories	Length (mm)	Quantity

Breezway Component System Information and Product Performance Warranty -
<https://www.breezway.com.au/technical/downloads/>



Altair Louvre Component Checklist

REQUIRED INFORMATION

Daylight Opening Height

Daylight Width

Gallery Colour

Clip & Handle Colour

OPTIONAL INFORMATION

If no selection is made, default option (indicated in brackets) will be supplied.

Control Side
(Left, as viewed from inside)

Screw Holes
(Yes)

Handle Type
(Standard Handle)

Restricted Opening
(No restriction)

Variable Handle Position
(Standard handle positions)

Keylock
(No)

OPTIONAL ACCESSORIES

Backing Strip
(Allows installation without visible screws)

Map Rod
(For operation of out of reach handles)

Security Jamb
(For security bars with no visible screws - must be

Security U-Channel
(For security bars with visible screws - can be installed after galleries and weatherstrips)

Powerlouvre Transformer
(Provides 24v DC current to Powerlouvre motors)

Breezway™ Altair® IGLU® System Standard Heights (mm)

No. of Blades	IGLU® Galleries with Weatherstrip	IGLU® Powerlouvre™ Galleries with Weatherstrip
2	335	365
3	475	505
4	615	645
5	755	785
6	895	925
7	1035	1065
8	1175	1205
9	1315	1345
10	1455	1485
11	1595	1625
12	1735	1765
13	1875	1905
14	2015	2045
15	2155	2185
16	2295	2325
17	2435	2465
18	2575	2605
19	2715	-
20	2855	-
21	2995	-