

## Standard Heights

Standard Height sizes are measured from bottom of visible metal to top of visible metal.

| Breezway™ Altair® IGLU® System Standard Heights (mm) |                                    |   |
|--|------------------------------------|---|
| No. of Blades  | IGLU® Galleries with Weatherstrip* | IGLU® Powerlouvre™ Galleries with Weatherstrip* |
| 2  | 335                                | 365   |
| 3  | 475                                | 505   |
| 4  | 615                                | 645   |
| 5  | 755                                | 785   |
| 6  | 895                                | 925   |
| 7  | 1035                               | 1065  |
| 8  | 1175                               | 1205  |
| 9  | 1315                               | 1345  |
| 10   | 1455                               | 1485  |
| 11   | 1595                               | 1625  |
| 12   | 1735                               | 1765  |
| 13   | 1875                               | 1905  |
| 14   | 2015                               | 2045  |
| 15   | 2155                               | 2185  |
| 16   | 2295                               | 2325  |
| 17   | 2435                               | 2465  |
| 18   | 2575                               | 2605  |
| 19   | 2715                               | –   |
| 20   | 2855                               | –   |
| 21   | 2995                               | –   |

\*Height without weatherstrip = -10mm for manual, -40mm for Powerlouvre™.

## Standard Widths

Opening Width when using Breezway Altair IGLU Galleries in Component Form

Daylight opening = IGLU Blade Length + 51mm

| Standard IGLU Blade Length | Daylight Opening Width |
|----------------------------|------------------------|
| 300mm                      | 351mm                  |
| 500mm                      | 551mm                  |
| 800mm                      | 851mm                  |
| 1,127mm                    | 1,178mm                |