

Altair® Louvre Windows

POCKET GUIDE

breezway

Altair® Louvre Window Standard Heights

No. of Blades	Easyscreen™ Window System Heights (For external screening)		Innoscreen® Window System Heights (For internal screening)		SL2® Window System Heights		Galleries only (Including Weatherstrip*)	
	Height 152mm	Height 102mm	Height 152mm	Height 102mm	Height 152mm	Height 102mm	Height 152mm	Height 102mm
2	371mm	-	380mm	-	358mm	-	330mm	-
3	511mm	361mm	520mm	370mm	498mm	348mm	470mm	320mm
4	651mm	451mm	660mm	460mm	638mm	438mm	610mm	410mm
5	791mm	541mm	800mm	550mm	778mm	528mm	750mm	500mm
6	931mm	631mm	940mm	640mm	918mm	618mm	890mm	590mm
7	1071mm	721mm	1080mm	730mm	1058mm	708mm	1030mm	680mm
8	1211mm	811mm	1220mm	820mm	1198mm	798mm	1170mm	770mm
9	1351mm	901mm	1360mm	910mm	1338mm	888mm	1310mm	860mm
10	1491mm	991mm	1500mm	1000mm	1478mm	978mm	1450mm	950mm
11	1631mm	1081mm	1640mm	1090mm	1618mm	1068mm	1590mm	1040mm
12	1771mm	1171mm	1780mm	1180mm	1758mm	1158mm	1730mm	1130mm
13	1911mm	1261mm	1920mm	1270mm	1898mm	1248mm	1870mm	1220mm
14	2051mm	1351mm	2060mm	1360mm	2038mm	1338mm	2010mm	1310mm
15	2191mm	1441mm	2200mm	1450mm	2178mm	1428mm	2150mm	1400mm
16	2331mm	1531mm	2340mm	1540mm	2318mm	1518mm	2290mm	1490mm
17	2471mm	1621mm	2480mm	1630mm	2458mm	1608mm	2430mm	1580mm
18	2611mm	1711mm	2620mm	1720mm	2598mm	1698mm	2570mm	1670mm
19	2751mm	1801mm	2760mm	1810mm	2738mm	1788mm	2710mm	1760mm
20	2891mm	1891mm	2900mm	1900mm	2878mm	1878mm	2850mm	1850mm
21	3031mm	1981mm	3040mm	1990mm	3018mm	1968mm	2990mm	1940mm
22	-	2071mm	-	2080mm	-	2058mm	-	2030mm
23	-	2161mm	-	2170mm	-	2148mm	-	2120mm
24	-	2251mm	-	2260mm	-	2238mm	-	2210mm
25	-	2341mm	-	2350mm	-	2328mm	-	2300mm
26	-	2431mm	-	2440mm	-	2418mm	-	2390mm
27	-	2521mm	-	2530mm	-	2508mm	-	2480mm
28	-	2611mm	-	2620mm	-	2598mm	-	2570mm
29	-	2701mm	-	2710mm	-	2688mm	-	2660mm
30	-	2791mm	-	2800mm	-	2778mm	-	2750mm
31	-	2881mm	-	2890mm	-	2868mm	-	2840mm
32	-	2971mm	-	2980mm	-	2958mm	-	2930mm
33	-	3061mm	-	3070mm	-	3048mm	-	3020mm

Glass, timber or aluminium



Control methods



Powerlouvre™ Window

Apptivate® Unit

Standard Handle



Ring Handle

Low Profile Handle

Innoscreen® Handle

Visit www.breezway.com.au or call 1800 777 758 for information

Altair® Louvre Window Systems

Easyscreen™ Window System

External screening which can integrate the Powerlouvre and Sub Framing for commercial use.

Innoscreen® Window System

Inside screening solution that maintains that 'louvre look' and is safer and easier to install.

SL2® Window System

Ideal for narrow frame applications where screening is not required.

Altair® Louvre Window Galleries

Wide range of gallery sizes that can be installed into a variety of window frames supplied by others.

FEATURED OPTIONS

Powerlouvre™ Window System

Motors concealed within the head of the frame and can be operated by the Powerlouvre™ Apptivate® Control Unit, the Powerlouvre™ App, in automatic response to temperature and timer settings or integrated into a Building Management System.

Stronghold® System

Mechanically retains louvre blades, providing extra strength and safety in multi-level buildings, balcony enclosures or school applications.



New Keylock

For Powerlouvre™ standard heights * To calculate the gallery height only, deduct 10mm

Note: Contact Breezway for Easyscreen™ or Innoscreen® Window Sub Framing instructions.

Passed cyclonic wind and water tests. Refer to Altair Product Performance Warranty.