

**Product Performance Warranty: Altair® IGLU® Louvres in Cyclonic Regions: Housing**

C1				C2				C3				C4			
General location		Corner Windows		General location		Corner Windows		General location		Corner Windows		General location		Corner Windows	
600 Pa SLS 1800 Pa ULS 150 Pa Water Pass		800 Pa SLS 2700 Pa ULS 150 Pa Water Pass		800 Pa SLS 2700 Pa ULS 200 Pa Water Pass		1200 Pa SLS 4000 Pa ULS 200 Pa Water Pass		1200 Pa SLS 4000 Pa ULS 300 Pa Water Pass		1800 Pa SLS 5900 Pa ULS 300 Pa Water Pass		1600 Pa SLS 5300 Pa ULS 450 Pa Water Pass		2500 Pa SLS 8000 Pa ULS 450 Pa Water Pass	
Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height	Max Blade Length	Max Height
mm	Blades	mm	Blades	mm	Blades	mm	Blades	mm	Blades	mm	Blades	mm	Blades	mm	Blades

**Altair IGLU Double Glazed Louvre<sup>2</sup>**

IGLU Blade (5LE/Ar/5LE)	800	21	800	21	800	21	800	21	500	11	500	11	500	11	500	11
IGLU Blade (5LE/Ar/5LE)	1127	13	1127	13	1127	13	–	–	–	–	–	–	–	–	–	–
Easyscreen Mullion <sup>1</sup>	–	21	–	18	–	18	–	16	–	17	–	14	–	10	–	7

**1. Mullions**

Mullion heights are based on a 1:250 deflection ratio and the maximum warranted louvre bay widths for each N or C rating and window location.

**2. Sills**

All IGLU Louvre assemblies must utilise the Breezway High Profile Sill