

Altair® Louvre Windows

POCKET GUIDE

breezway

Glass, timber or aluminium




Control methods



Powerlouvre™ Window

Apptivate® Unit

Standard Handle



Ring Handle



Low Profile Handle



Innoscreen® Handle

Visit www.breezway.com.au or call 1800 777 758 for information

Altair® Louvre Window Systems

Easyscreen™ System

External screening which can integrate the Powerlouvre and Sub Framing for commercial use.

SL2® System

Ideal for narrow frame applications where screening is not required.

Altair® Galleries

Range of sizes that can be installed into window frames supplied by others.

FEATURED OPTIONS

Powerlouvre™ Window

Can be operated by the Apptivate® Control Unit or Powerlouvre™ App, in automatic response to temperature and timer settings or integrated into a Building Management System.

Stronghold® System

Mechanically retains louvre blades, providing extra strength and safety in multi-level buildings, balcony enclosures or school applications.

Innoscreen® System

Inside screening solution that maintains that 'louvre look' and is safer and easier to install.

Dualair® System

Provides improved water performance, sound reduction, thermal insulation, shading capabilities and excellent ventilation.

Altair® Louvre Window Standard Heights

Height	Easyscreen™ Window System (External Screen Pocket)		Innoscreen® Window System (Internal Screen Pocket)		SL2® Window System		Dualair® Secondary Glazing System*	Altair® Louvre Galleries Component System (with weatherstrip**)		Altair® Powerlouvre™ Galleries Component System (with weatherstrip***)	
	102mm	152mm	102mm	152mm	102mm	152mm	152mm	102mm	152mm	102mm	152mm
No. of Blades	ALL DIMENSIONS IN MM										
2	-	371	-	380	-	358	418	-	330	-	360
3	361	511	370	520	348	498	558	320	470	350	500
4	451	651	460	660	438	638	698	410	610	440	640
5	541	791	550	800	528	778	838	500	750	530	780
6	631	931	640	940	618	918	978	590	890	620	920
7	721	1071	730	1080	708	1058	1118	680	1030	710	1060
8	811	1211	820	1220	798	1198	1258	770	1170	800	1200
9	901	1351	910	1360	888	1338	1398	860	1310	890	1340
10	991	1491	1000	1500	978	1478	1538	950	1450	980	1480
11	1081	1631	1090	1640	1068	1618	1678	1040	1590	1070	1620
12	1171	1771	1180	1780	1158	1758	1818	1130	1730	1160	1760
13	1261	1911	1270	1920	1248	1898	1958	1220	1870	1250	1900
14	1351	2051	1360	2060	1338	2038	2098	1310	2010	1340	2040
15	1441	2191	1450	2200	1428	2178	2238	1400	2150	1430	2180
16	1531	2331	1540	2340	1518	2318	2378	1490	2290	1520	2320
17	1621	2471	1630	2480	1608	2458	2518	1580	2430	1610	2460
18	1711	2611	1720	2620	1698	2598	2658	1670	2570	1700	2600
19	1801	2751	1810	2760	1788	2738	-	1760	2710	-	-
20	1891	2891	1900	2900	1878	2878	-	1850	2850	-	-
21	1981	3031	1990	3040	1968	3018	-	1940	2990	-	-
22	2071	-	2080	-	2058	-	-	2030	-	-	-
23	2161	-	2170	-	2148	-	-	2120	-	-	-
24	2251	-	2260	-	2238	-	-	2210	-	-	-
25	2341	-	2350	-	2328	-	-	2300	-	-	-
26	2431	-	2440	-	2418	-	-	2390	-	-	-
27	2521	-	2530	-	2508	-	-	2480	-	-	-
28	2611	-	2620	-	2598	-	-	2570	-	-	-
29	2701	-	2710	-	2688	-	-	2660	-	-	-
30	2791	-	2800	-	2778	-	-	2750	-	-	-
31	2881	-	2890	-	2868	-	-	2840	-	-	-
32	2971	-	2980	-	2958	-	-	2930	-	-	-
33	3061	-	3070	-	3048	-	-	3020	-	-	-

■ For Powerlouvre™ standard heights

* Head: Alspec McArthur EVO. Sill/Transom: Alspec McArthur EVO

** To calculate the gallery height only, deduct 10mm

Note: Contact Breezway for Easyscreen™ or Innoscreen® Window Sub Framing instructions.

Passed cyclonic wind and water tests. Refer to Altair Product Performance Warranty.