

Altair® Louvre Windows

POCKET GUIDE



breezway®

Altair® Louvre Window Standard Heights

	Easyscreen™ Window System (External Screen Pocket)			Innoscreen® Window System (Internal Screen Pocket)		SL2® Window System		Dualair® Secondary Glazing System*	Altair® Louvre Galleries Component System (with weatherstrip**)			Altair® Powerlouvre™ Galleries Component System (with weatherstrip***)		
Height	102mm	152mm	-	102mm	152mm	102mm	152mm	152mm	102mm	152mm	-	102mm	152mm	-
No. of Blades	IGLU® System			ALL DIMENSIONS IN MM									IGLU® System	IGLU® System
2	-	371	376	-	380	-	358	418	-	330	335	-	360	365
3	361	511	516	370	520	348	498	558	320	470	475	350	500	505
4	451	651	656	460	660	438	638	698	410	610	615	440	640	645
5	541	791	796	550	800	528	778	838	500	750	755	530	780	785
6	631	931	936	640	940	618	918	978	590	890	895	620	920	925
7	721	1071	1076	730	1080	708	1058	1118	680	1030	1035	710	1060	1065
8	811	1211	1216	820	1220	798	1198	1258	770	1170	1175	800	1200	1205
9	901	1351	1356	910	1360	888	1338	1398	860	1310	1315	890	1340	1345
10	991	1491	1496	1000	1500	978	1478	1538	950	1450	1455	980	1480	1485
11	1081	1631	1636	1090	1640	1068	1618	1678	1040	1590	1595	1070	1620	1625
12	1171	1771	1776	1180	1780	1158	1758	1818	1130	1730	1735	1160	1760	1765
13	1261	1911	1916	1270	1920	1248	1898	1958	1220	1870	1875	1250	1900	1905
14	1351	2051	2056	1360	2060	1338	2038	2098	1310	2010	2015	1340	2040	2045
15	1441	2191	2196	1450	2200	1428	2178	2238	1400	2150	2155	1430	2180	2185
16	1531	2331	2336	1540	2340	1518	2318	2378	1490	2290	2295	1520	2320	2325
17	1621	2471	2476	1630	2480	1608	2458	2518	1580	2430	2435	1610	2460	2465
18	1711	2611	2616	1720	2620	1698	2598	2658	1670	2570	2575	1700	2600	2605
19	1801	2751	2756	1810	2760	1788	2738	-	1760	2710	2715	-	-	-
20	1891	2891	2896	1900	2900	1878	2878	-	1850	2850	2855	-	-	-
21	1981	3031	3036	1990	3040	1968	3018	-	1940	2990	2995	-	-	-
22	2071	-	-	2080	-	2058	-	-	2030	-	-	-	-	-
23	2161	-	-	2170	-	2148	-	-	2120	-	-	-	-	-
24	2251	-	-	2260	-	2238	-	-	2210	-	-	-	-	-
25	2341	-	-	2350	-	2328	-	-	2300	-	-	-	-	-
26	2431	-	-	2440	-	2418	-	-	2390	-	-	-	-	-
27	2521	-	-	2530	-	2508	-	-	2480	-	-	-	-	-
28	2611	-	-	2620	-	2598	-	-	2570	-	-	-	-	-
29	2701	-	-	2710	-	2688	-	-	2660	-	-	-	-	-
30	2791	-	-	2800	-	2778	-	-	2750	-	-	-	-	-
31	2881	-	-	2890	-	2868	-	-	2840	-	-	-	-	-
32	2971	-	-	2980	-	2958	-	-	2930	-	-	-	-	-
33	3061	-	-	3070	-	3048	-	-	3020	-	-	-	-	-

For Powerlouvre™ Standard Heights.

- * **Head:** Alspec McArthur EVO.
- Sill/Transom:** Alspec McArthur EVO.
- ** To calculate the gallery height only, deduct 10mm.
- *** To calculate the gallery height only, deduct 40mm.
- Note:** Contact Breezway for Easyscreen™ or Innoscreen® Window Sub Framing instructions.

GLASS, TIMBER or ALUMINIUM



CONTROL METHODS



Powerlouvre™ System



Apptivate® Unit



Standard Handle



Ring Handle



Low Profile Handle



Innoscreen® Handle

FOR MORE INFORMATION

www.breezway.com.au
or call 1800 777 758

FEATURED OPTIONS

Powerlouvre™ System

Operated by the Apptivate® Control Unit or Powerlouvre™ App, in automatic response to temperature and timer settings or integrated into a Building Management System.

Stronghold® System

Mechanically retains louvre blades, providing extra strength and safety in multi-level buildings, balcony enclosures or school applications.

Dualair® System

A secondary glazed system which improves sealing, sound reduction, thermal insulation, shading capabilities and has excellent ventilation.



NEW IGLU® System

Double glazed louvre unit that is fall prevention compliant offering excellent ventilation and improved thermal insulation.